



► Features

- High-quality 2-way loudspeaker
- Attractive design
- True-to-nature sound reproduction
- Heat resistant up to 100°C
- Humidity resistant
- Polypropylene cone
- Silicone connection cable
- IP44

► Applications

- Sauna's
- Swimming pool area
- Wellness centers
- Outdoor area's
- ...

The SSP500 is a flush mount loudspeaker, especially designed to be used in rooms with a very high temperature and level of humidity, such as Sauna's, bathrooms, swimming pool area's, ...

It has a perforated aluminum grill with an ABS surround, finished in an off-white color. This gives the loudspeaker a modern and attractive look, making it blend into all different kinds of interiors. To make it even more complementary to the environment, the front can easily be painted to the desired colour.

The sound is generated by a 2-way loudspeaker section capable of producing a power of 20 Watt RMS, which is built from a 5" cone driver and a 1" tweeter, producing a natural and detailed sound which overall will be highly appreciated.

Due to the polypropylene cone, the ABS basket and the high quality of the used materials, the SSP500 can withstand in environments with extreme levels of humidity and temperature.

► Specifications

SYSTEM SPECIFICATIONS	
Max. power	40 W
RMS power	20 W
Impedance	8 Ohm
Sensitivity (1W / 1m)	86 dB
Sound Pressure Max (Max W / 1m)	99 dB
Freq. Response (±3 dB)	75Hz - 20 kHz
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	Ø 175 x 74 mm
Weight net	0.62 Kg
Drivers (Coaxial)	HF LF
Construction	Heat resistant ABS housing
Mounting	4 Screws
Cut out measurement	Ø 120 mm
Built-in depth	60 mm
Front finish	White aluminium grill
Colour	White (RAL 9010)
Operation temperature range	-25 °C ~ 100°C
Operation relative humidity	< 95 %
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	Kg - Cbm
Accessories	Cut-out template

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products