

CSF506

Fire Protected Ceiling Speaker

AUDAC

► Features

- Steel fire protection dome
- Two power taps
- Steel front grill
- Flame retardant materials
- Ceramic connection block
- Thermal fuse

► Applications

- All applications where built-in speakers are needed for evacuation purposes



The CSF506 is a fire-protected ceiling speaker with a 5" cone, capable of producing a power of 6W.

It ensures a good reproduction of speech and alarm signals for evacuation purposes. It is fitted with a 100V line transformer with power taps for 6W and 3W to be used in large 100V PA systems.

The speaker is equipped with a special steel fire protection dome fitted around the speaker and a steel front grill with flame retardant materials.

The connections of the loudspeaker are performed using a ceramic connection block and the thermal fuse ensures that in case of fire the loudspeaker will be disconnected from the circuit.

Hereby, the other loudspeakers on the same circuit will keep on operating.

► Specifications

SYSTEM SPECIFICATIONS	
Max. power	10 W
RMS power	6 W
Line voltage	100 V
Power taps	6 W / 1666 Ohm 3 W / 3333 Ohm
Impedance	8 Ohm
Frequency response -3dB	90 Hz - 18 kHz
Sound pressure W/1m	90 ± 3 dB
PRODUCT FEATURES	
Dimensions (Diameter x Depth)	Ø 180 x 127 mm
Cut-out measurement	Ø 160 mm
Weight net	1.3 Kg
Drivers	5"
Construction	Steel
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	